

## Joint brusher FBM 300



### For cleaning and chamfering joints and enlarging cracks

- Optimum weight distribution for rapid repositioning and set-up.
- Height adjustability and positioning of handlebars for a perfect view of the tool.
- Continuous oil supply extends the service life of the horizontally mounted motor - this also increases the air filter maintenance intervals.
- The adjustable front axle eliminates leverage effect due to floor unevenness - this guarantees uniform processing of the joint.
- Comes as standard with parking brake and stepless threaded spindle for setting the working depth
- An optional LED working light, in combination with the generator kit, is recommended for use at night or in a tunnel
- Crane eyes for simple unloading and transport
- Detachable brush guard with left and right adjustable deflectors.
- Waste collector basket to catch debris from joint - prevents stone chips
- The tool cutting direction is opposite to the direction of movement so dirt is not guided towards the fresh cut area.

**Technical details:**

Description	FBM 300 P	FBM 300 D
Article-Nr.	018M 0033	018M 0049
Brush width	6-18 mm	6-18 mm
Brush depth	60 mm	60 mm
Brush Ø	300 mm	300 mm
Holder	20.0 / 25.4 mm	20.0 / 25.4 mm
Fuel	petrol	diesel
Output power max.	8.7 kW / 11.8 hp	7.3 kW / 9.8 hp
Speed	2800 1/min	2800 1/min
Length ca.	1.300 mm	1.300 mm
Width ca.	650 mm	650 mm
Height ca.	930 mm	930 mm
Weight	115 kg	137 kg

Subject to technical changes!