

Dry joint cutter Dicorona 514-S



Especially suitable for the wall- and curb flush cutting of construction joints.

- Manoeuvrable and easy-to-use machine
- Consistently well-suited for dry cutting
- Integrated dust extraction
- Hydraulic blade positioning by lowering valve and push-button switch
- Reliable visual contact with the diamond saw blade when setting up the machine
- Equipped with larger suction unit and double cyclone filter system to maximize dust extraction
- The bevel cut equipment allows set the machine to a max. 5 degrees angel for cutting wall- or curb flush joints.

Delivery **without** cutting disc!

Technical details:

Description	DICORONA 514 S
Item-Nr.	018M 0039
Engine	2-cylinder petrol engine with electric start 27,2 kW at 3600 rpm
Traction-drive	Adjustable up to approx. 30 m/min. with rear axle steering
Blade diameter	350 mm
Maximum cutting depth	approx. 90 mm
Bevel adjustment	with a spindle for mechanical adjustment, max. 5 degrees
Blade rising and lowering	hydraulic with lowering valve
Weight	approx. 363 kg
Length	approx. 1.300 mm
Width	approx. 630 mm
Height	approx. 1.310 mm

Accessoires:

Diamond cutting disc 350 x 4,3 x 25,4	Art.-Nr. 018W 0000
Diamond cutting disc 350 x 6,0 x 25,4	Art.-Nr. 018W 0000
Diamond cutting disc 350 x 8,0 x 25,4	Art.-Nr. 018W 0000

Subject to technical changes!