

Disc crack cutter 5060S



With propulsion and hydraulic quick lift

- Environmentally friendly dry crack cutter for low-cost expansion of uneven running stress cracks in road surfaces and for creating expansion joints
- Dry cutting method with dust extraction
- Low deadweight
- Special design makes following “wild cracks” no trouble at all.
- Cutting expansion joints
- Infinitely adjustable depth setting, max. 50 mm with 200 mm cutting disc
- Propulsion makes for easy and effortless work.
- Infinitely adjustable cutting speed

Technical Details

Disc crack cutter 5060S

Item no.	5360 0000
Drive engine 2-cylinder Vanguard petrol engine	16.9 kW
Length approx.	1270 mm
Width approx.	670 mm
Height approx.	1370 mm
Deadweight approx.	230 kg

Accessoires

Diamond cutting disc for asphalt

approx. 150 x 15 x 25.4 mm/cutting width 15/8 mm	5068 8200
approx. 200 x 10 x 25.4 mm/cutting width 10 mm	5060 8100
approx. 200 x 6 x 25.4 mm/cutting width 6 mm	5060 8200
approx. 150 x 30 x 25.4 mm/cutting width 15 mm	5060 8300
Protective cover for flush-to-the-wall cutting disc	5360 1100
Protective cover for 200 mm disc	5360 1003
Brushes for protective cover 150 mm	5360 1002
Brushes for protective cover 200 mm	5360 1004
Wear parts kit	5360 9900