Sealing compound boiler VK 50 HR with temperature regulator

For melting bituminous joint sealing material.

- Propane vortex beam burner with ignition burner, temperature regulator, piezo ignition and temperature indicator with drain cock for taking out the melted material
- Safety pilot
- Double-wall insulation of outer casing of the pot
- Flame-shield in the combustion chamber – Hot-air heating-

Technical details:

Description	VK 50 HR stationary	VK 50 HR with manual driving assembly
Item no.	83710 0100	83711 0100
Boiler capacity	50 L	50 L
Heating	Indirect heating by flame-shield	Indirect heating by flame-shield
Burner power	11 kW	11 kW
Temperature indicator	yes	yes
Temperature control	yes	yes
Model	stationary	manual driving unit
Agitator	manual agitator	manual agitator
Approx. length	770 mm	1110 mm
Approx. height	1050 mm	1250 mm
Approx. width	720 mm	720 mm
Approx. unloaded weight	54 kg	66 kg

Accessories:

GRÜN GmbH Spezialmaschinenfabrik
Siegener Straße 81 - 83 • 57234 Wilnsdorf-Niederdielfen
Tel.: +49 (0) 271 - 39 88-0 • **Fax:** +49 (0) 271 - 39 88-159

www.gruen-gmbh.de • info@gruen-gmbh.de

3 m high pressure hose including 1.5 bar regulator	1501 0000	1501 0000
3 m high pressure hose including 1.5 bar regulator	1502 0000	1502 0000

Subject to technical changes.

GRÜN GmbH Spezialmaschinenfabrik
Siegener Straße 81 - 83 • 57234 Wilnsdorf-Niederdielfen
Tel.: +49 (0) 271 - 39 88-0 • **Fax:** +49 (0) 271 - 39 88-159

www.gruen-gmbh.de • info@gruen-gmbh.de