

RTK 250 to RTK 1800 horizontal, stationary



Equipment for melting and processing thermoplastic road marking materials and bituminous joint, rail sealing and railway grouting materials

- Compact design
- High melting performance for powder or block materials with low gas/heating oil consumption
- Boiler shell made of wear-resistant and heat-resistant special steel
- Quick heat-up time
- Horizontal, hydraulically driven agitator, electrically switchable
- Indirect heating by flame-shield/flue gas chamber

Technical details:

Description	RTK 250	RTK 500	RTK 800	RTK 1300	RTK 1800
Item no. RTK oil firing	-----	84005 0000	84008 0000	84013 0000	84018 0000
Item no. RTK gas firing	84003 0100	84005 0200	84008 0200	84013 0200	84018 0200
Boiler capacity	250 L	500 L	800 L	1.3 m ³	1.8 m ³
Diesel motor power	3.1 kW at 3000/min	5.2 kW at 3000/min	5.2 kW at 3000/min	5.2 kW at 3000/min	5.2 kW at 3000/min
Supra Silent Pack	no	yes	yes	yes	yes
Burner power	40 kW	70 kW	90 kW	100 kW	100 kW
Agitator speed	2-7/min	2-7/min	2-7/min	2-7/min	2-7/min
Thickness of the boiler shell	6 mm	6 mm	6 mm	6 mm	6 mm
Approx. length	1860 mm	2640 mm	2600 mm	3170 mm	3870 mm
Approx. width	1200 mm	1150 mm	1250 mm	1450 mm	1450 mm
Approx. height	1530 mm	1480 mm	1480 mm	1480 mm	1480 mm
Unloaded weight approx.:	800 kg	1300 kg	1420 kg	1980 kg	2600 kg

Subject to technical changes.