

AHS 5-200 bitumen spraying machine



For spraying primer and bitumen emulsions.

AHS 5-200 bitumen spraying machine

For spraying primer and bitumen emulsions.

- Trailer bitumen spray machine with holder for 200 L barrel including vehicle lighting, car coupler and truck coupling ring, hand-pull drawbar double brake function, maximum speed with full tank 80 km/h
- Binding material pump with pressure relief valve and hydraulic drive to enable back suction and circulation of binding material, no direct belt drive.
- The exhaust from the diesel engine heats the binding material pump and the 200 L barrel with the binding material is warmed by a propane gas burner system. The manual gas burner system is equipped with all necessary safety devices and piezoelectric ignition.
- Diesel engine with recoil starter.
- The delivery includes a 5 m spray hose and spray lance for applying the binding material

Technical details:

Description	AHS 5-200
Part no.	0344 0000
Diesel engine type	HATZ 1B20
Diesel engine power	3,5 kW at 3.600 1/min
Drive of the binding material pump	Hydraulic
Max. Approx. capacity of binding material pump	16 L/min
Approx. power of propane gas heating	10 kW
Propane gas bottle holder	For one 11 kg propane gas bottle
Approx. length	3.000 mm
Approx. width	1.300 mm
Approx. height	1.250 mm
Approx. deadweight	380 kg
Total permissible weight:	500 kg

Subject to technical changes.

Thanks to many years of cooperation of Mr. Maximilian Straßmayr, co-founder and former managing director of Straßmayr GmbH Adlwang Austria, who held the position as the technical manager in the field of bitumen emulsion and patch technology, we successfully established ourselves in the market and complete numerous projects with success.